ViewSonic® on top!

M70 Monitor

MultiMedia Series

(PC Sold Separately)

- **0.27mm dot pitch**
  This fine dot pitch produces clear, crisp images with great picture definition, even at the highest resolutions.

- **1,280 x 1,024 maximum resolution**
  Displays a maximum resolution of 1,280 x 1,024; 1,024 x 768 at 87Hz flicker-free refresh rate for easy viewing.
  1,280 x 1,024 @ 66Hz
  1,024 x 768 @ 87Hz
  800 x 600 @ 110Hz
  640 x 480 @ 135Hz

- **Flat square screen**
  Ergonomically designed to provide full image display with minimal glare/distortion on edges and corners. Displayed images remain true in size and proportion throughout the screen.

- **Bezel-integrated high-fidelity speakers and microphone**
  Two powerful 2.0W speakers produce stereo sound with superior quality for demanding multimedia applications. A built-in microphone allows bi-directional communication in true multimedia applications such as video conferencing and computer telephony.

- **Available in black case**

- **PC and Mac® compatible**

- **Three year limited warranty**

17" (16.0" viewable) Monitor

An exciting multimedia experience can be yours with the new ViewSonic M70 monitor. Equipped with two powerful 2W speakers, built-in microphone and headphone jack, the M70 will not only enhance your computing experience, but the space saving design will reduce desk clutter. This 17" (16.0" viewable) monitor is the ideal choice for a variety of applications, including gaming, surfing the Internet, general business and teleconferencing. To provide sharp, crisp screen images with true brilliant colors, this monitor has been designed with a fine 0.27mm dot pitch. Supported by a limited three year warranty and 24 hour technical support rounds out a multimedia experience you won't want to miss.

ViewSonic on top™

www.ViewSonic.com

ViewSonic®

M70 Monitor

M70B Black Case version

- **OnView® controls including ViewMatch®**
  All screen adjustments are made via an on screen menu using simple controls. ViewMatch allows the user to adjust color temperature and individual color intensity for screen-to-print matching.
- **Anti static, anti glare screen**
  This anti static, anti glare screen coating refracts unwanted light away from the user while maintaining the highest quality of the displayed image.
- **Headphone jack and external microphone port**
  Easily accessible headphone and microphone jacks give users the flexibility of adding external multimedia devices.
- **Invar shadow mask**
  A special type of alloy that withstands higher heat levels, extending the picture tube life while displaying sharp, bright pictures.
- ***Plug & Play +***
  Fully supports the Windows® 95 auto installation standard for easy, trouble-free configuration and setup.

17" (16.0" VIEWABLE) MULTIMEDIA COLOR MONITOR WITH *Plug & Play +*

CRT	**Type**	17" (16.0" diagonal viewable area) 0.27mm dot pitch, 90° deflection
	Phosphor	RGB medium persistence
	Glass Surface	Tint (TM up to 53%) anti-static, anti-glare coating
INPUT SIGNAL	**Video**	RGB analog (0.714Vp-p, 75 ohms)
	Sync	H/V separate (TTL), sync-on-green, composite
	Frequency	F_h:30-70kHz, F_V:50-160Hz
	Audio	1.0Vrms
COMPATIBILITY	**PC**	IBM® PC and PC compatibles (from VGA up to 1,280 x 1,024 non-interlaced)
	Mac®*	Power Mac™ (up to 1024 x 768)
CONNECTOR	**Video In**	15-pin mini D-sub, (attached)
	Audio In	3.5mm pin mini jack (stereo)
	Mic In/Out	3.5mm pin mini jack (mono/auxillary)
	Headphone Out	3.5mm pin mini jack (stereo)
	Power	3-pin plug (IEC320)
POWER	**Voltage**	AC 80-240VAC/50-60Hz (auto switch)
	Consumption	125W (typ)
USER CONTROLS	**Basic**	Power on/off, enter, volume, +/-, mute, 1, up, down, 2
	OnView®	Contrast, brightness, H/V-size, H/V-position, pincushion, pin-balance, trapezoid, parallelogram, tilt, moiré, ViewMatch® color, degauss, ViewMeter®, OSD position, language, audio, recall, volume
VIDEO INPUT	**Bandwidth**	110MHz (typ)
AUDIO	**Output**	2W (x2) @ 1KHz, THD:10%
	Response	200Hz-20kHz +/-3dB
MISCONVERGENCE		0.3mm (max) at center, 0.4mm (max) at corner
DISPLAY AREA	**Factory Setting**	265mm (H) x 198mm (V) (Dependent upon
	Maximum Scan	280mm (H) x 210mm (V) signal timing used)
OPERATING CONDITION	**Temperature**	32°F to 104°F (0°C to 40°C)
	Humidity	5% to 95% (non condensing)
DIMENSIONS	**Physical**	412mm (W) x 405mm (H) x 426mm (D) (16.2 x 15.9 x 16.8)
WEIGHT	**Net**	16.5Kg (36.3 lbs.)
OTHER		DDC1 & DDC2B, PC '99 compliance
REGULATIONS		UL, CSA, DHHS, MPR-II, ISO9241-3, TUV/GS, DOC-B, EN60950, CE, BCIQ, TCO '92, C-Tick, NEMKO, DEMKO, SEMKO, FIMKO
POWER MANAGEMENT		Meets Energy Star®, VESA® and DPMS™ standards
WARRANTY		Three year limited warranty on CRT, parts and labor 48 hour Express Exchange® service option available

ISO 14001 EMS 40968

ISO 9001 FM 40187

ViewSonic Corporation's QMS\EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

ViewSonic on top™

www.ViewSonic.com
381 Brea Canyon Road, Walnut, CA 91789
Phone (800) 888-8583 • (909) 869-7976
Fax (909) 869-7958 • Internet: www.ViewSonic.com

*Free universal Mac® cable adapter available.

Copyright © 1999, ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies. Specifications subject to change without notice. The EPA only promotes energy efficiency and does not endorse any particular company or product. Microsoft, Windows, Windows NT and the Windows logo are the registered trademarks of Microsoft Corporation in the United States and other countries.
VSM70-7/99-20K-rev1